



TECHNICAL SPECIFICATION

Built	11/2002 (Kanasashi Heavy Industries Japan)
Classification	NK
Length overall (m)	182.98
Breadth Moulded (m)	31.0
Depth Moulded (m)	16.671
Total Hold Capacity (m3)	59,077.36
Deadweight (t)	46,673
Summer Draft (m)	11.671
Gross Tonnage	26,195
Net Tonnage	15,577
Hatches / Holds	5 / 5
Cranes	4 x 30 SWL

MV *Mareeba* is a conventional handymax bulk carrier that operates on the Australian coast. The vessel carries primarily, gypsum, clinker, dolomite, sugar, salt and coal.

MV *Mareeba* discharges using four cranes of 30mt SWL, with four 12m³ remote controlled grabs.

HATCH AND HOLD SPECIFICATIONS

HOLD VOLUMES (CUBIC METRES)

HOLD NUMBER	1	2	3	4	5	TOTAL
Cubic (Grain)	10,518.78	12,438.44	11,829.07	12,785.91	11,505.16	59,077.36
Cubic (Bale)	10,236.40	12,223.17	11,631.56	12,569.56	11,353.32	58,014.01

HOLD OPENINGS (METERS)

NUMBER OF OPENINGS	1	1	1	1	1
Opening Length	14.40	20.00	20.00	20.00	20.00
Opening Width	15.50	15.60	15.60	15.60	15.60
Coaming height above keel	18.77	18.77	18.77	18.77	18.77

CARGO HANDLING EQUIPMENT

4 x 30t Electro Hydraulic cranes

4 x 12 m³ grabs

CONSUMPTION (TONNES PER DAY)

	SPEED		MAIN ENGINE HFO		A/E
	Loaded	Ballast	Loaded	Ballast	HFO
Sea	13.0	13.5	25.1	23.2	1.5
Port/ Anchorage			N/A	N/A	2.4
Loading/ Discharge			N/A	N/A	2.4 / 5.1

All specifications given in good faith but without guarantee.